



GREEN COMPOSTER 330 FOR TOILET WASTE



The Green Composter 330 is a closed composter designed for composting toilet waste into soil. It can be used for the waste from freezing toilets, small chamber pots, urine separating toilets, or other dry toilets.

Contents:

- Composter, double base and lid
- Liquid hose and canister
- Wheels
- Bag of dry material

If the volume of the Green Composter is sufficient, it can also be used for composting kitchen organic waste and garden waste.

Made in Finland.

Starting the Use of the Green Composter 330

The composting power and the liquid treatment of the Green Composter are based on a capillary double base. **It works like a self-watering flower pot:** part of the liquid is absorbed back into the compost mass, thus accelerating the composting process. To ensure proper absorption, it is important to cover the false base with peat, saw dust or other dry material.

1. Start using the toilet by placing about 5-10 cm of cover material on the false base.

Also, fill the hollow legs of the double base tightly with cover material. Remember to repeat this after each emptying.



2. Connect the liquid hose to the liquid outlet at the bottom of the container and place the other end in the canister. The canister and hose should be placed lower than the composter to allow excess liquid (seap liquid) to flow out.



3. Place the wheels to the slot at the bottom.

After this, you can start adding waste to the composter.

During Use

If the waste added to the composter is too wet, regularly add more dry material to the composter.

Remember to monitor the seap liquid canister. When it starts to fill up, pour the excess liquid back into the composter if the mass seems dry. Alternatively, use it in the garden as a fertilizer directly on trees or bushes. However, do not pour it on edible plants, and avoid areas near water bodies or wells.

It is important for composting process that the compost mass is not too dense. Therefore, regularly use the composter's mixer or garden fork to aerate the mass.

If flies appear in the compost, cover them with dry material.

Composting of toilet waste usually takes 6-14 months depending on the conditions. It is recommended to keep the composter in a sunny location to speed up the process with the sun's heat.

When you want to empty the composter, move it close to the emptying spot using the wheels and empty it by tilting the container. Remember to cover the double bottom again after emptying.

For more information and quality supplies for composting, visit Pikkuvihreä!

